

MOTUL 300V LE MANS 10W-60

Car racing motor oil Ester Core®

TYPE OF USE

All racing gasoline or Diesel engines, naturally aspirated, turbocharged or supercharged fitted with injection (direct/indirect) or carburetted

For tuned engines and high performance cars operating over a wide range of rpm and temperatures, in severe driving conditions.

Suitable for all types of fuels, gasoline, Diesel and biofuels (especially Ethanol).

PERFORMANCES

STANDARDS

Above existing standards

<u>TYPE OF USE</u>: Circuit, Drag race, Drift, Endurance, GT, Hill climb, Historic racing, Rally, Rally cross, Track days, Tuning... Consult your tuning service partner for appropriate type of use.

ESTER Core® Technology

For decades MOTUL has developed high performance synthetic Ester based lubricants.

The **300V** Line includes the latest evolutions of MOTUL's proprietary **ESTER** Core® Technology to ensure maximum engine power output without compromising reliability and wear protection. MOTUL has created a perfect synergy formula to increase performance and protection of the engine selecting esters over other high performance synthetic and organic base stocks and combining them with an innovative additive package. This exclusive Racing formulation now features biofuels (especially Ethanol) and particulate filter compatibility, LSPI protection and lowers its environmental impact.

Esters are polar molecules hence are attracted to metallic surfaces. *ESTER* Core[®] Technology features optimized polarity for maximal adherence of the oil film to increase engine protection, reliability and driveability, even in most extreme conditions.

Used only in the **300V** range, this exclusive technology guarantees you more:

• Maximum power output: Friction reduction for maximum power and torque at all rpm

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.



MOTUL 300V LE MANS 10W-60

Car racing motor oil Ester Core®

- Reliability: High shear stability for maximal oil film resistance to reduced engine wear
- Life: Increased oxidation resistance for longer engine & oil life duration
- Driveability: Maximal polar adherence of the oil film for rapid engine rpm response
- Easy start: Fast oil pressure build-up and optimal oil flow
- Reduced oil consumption: Low oil volatility and evaporation helps to control oil consumption
- Detergency: High detergency performance allows better engine cleanliness
- Driving comfort: Lower friction level brings engine noise reduction in all driving modes

This racing formulation **300V** with exclusive **ESTER** Core[®] Technology features biofuels and particulate filter compatibility and LSPI protection.

- Biofuels: Compatible with alcohol-based fuels, especially Ethanol (up to E85)
- LPSI protection: Compatible with downsized engines subjected to Low Speed Pre-Ignition issues
- <u>Particulate filter:</u> Compatible with particulate filter requiring reduced SAPS (Sulfated Ash, Phosphorous, Sulfur) level (SAPS: 0.91% weight and TBN: 8.1 mg KOH/g)



ORGANIC BASE

The Organic base using non-fossil renewable materials is limiting the environmental impact and allows MOTUL to lower its carbon footprint by 25% during manufacturing process.

The **300V** LE MANS series viscosity grades allow stable oil pressure and bring the maximum reliability to your engine in all extreme conditions.

These **300V** LE MANS series viscosity grades can cope with engines subject to high engine oil dilution from unburned fuel and are suitable for engines featuring high clearances.

RECOMMENDATIONS

- MOTUL 300V LE MANS series are suitable for some engine applications and are particularly recommended for endur-

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.



MOTUL 300V LE MANS 10W-60

Car racing motor oil Ester Core®

ance, drift... etc, or historic racing engines (rebuilt engines) requiring high protection against wear and very stable and consistent oil pressure.

- Adapt or choose the right **300V** viscosity grade according to the viscosity grade recommended in your owner's manual or by your tuning service partner.
- To guarantee optimal engine performance, avoid mixing with other synthetic or mineral lubricants.
- Oil Change: Consult your tuning service partner for appropriate drain interval and tune to your own use.

PROPERTIES

| Viscosity grade | SAE J 300 | |
|---------------------------------|------------|---------------------|
| | | 10W-60 |
| Density at 20°C (68°F) | | 0.854 |
| | ASTM D445 | 162.1 mm²/s |
| Viscosity at 40°C (104°F) | | |
| | ASTM D445 | 23.6 mm²/s |
| Viscosity at 100°C (212°F) | | |
| HTHS viscosity at 150°C (302°F) | ASTM D4741 | 5.5 mPa.s |
| | ASTM D2270 | 176.0 |
| Viscosity Index | | |
| | ASTM D97 | -36.0 °C / -33.0 °F |
| Pour point | | |
| Flash point | ASTM D92 | 234.0 °C / 453.0 °F |